



IceMaster M+S



Product features



Multi-directional groove distribution design:
It is beneficial to improve the stability of driving in the ice and the safety of driving.



Diamond Angle cutting design
Can effectively pierce through the water film, stabilize on ice and improve the anti-slip effect.



High-density 3D steel sheet design
While ensuring the softness of the grounding surface of the tire, it also increases the strength of the overall pattern block to ensure super grip and reduce the feeling of driving lag.



High-score white carbon black formula design
Improve tire grip in cold environments and ensure tire safety performance at low temperatures.



DRAINAGE



STABILITY



BRAKING



SNOW&ICE



WINTER

Size	Loading Index	Speed Rating	Tread Depth	Inflatable Section Width(mm)	Standard Rim	Overall Diameter (mm)	MAX Load Kg	MAX Pressure Kpa	MAX Pressure Psi	Sidewall Description
165/70R13	79	S	8.5	170	5J	562	437	963	300 44	BSW
175/70R13	82	S	8.3	177	5J	576	475	1047	300 44	BSW
175/65R14	82	S	8.3	177	5J	584	475	1047	300 44	BSW
175/70R14	84	S	8.5	177	5J	602	500	1102	300 44	BSW
185/60R14	82	S	8.3	189	5 1/2J	578	475	1047	300 44	BSW
185/65R14	86	S	8.3	189	5 1/2J	596	530	1168	300 44	BSW
185/70R14	88	S	8.5	189	5 1/2J	616	560	1235	300 44	BSW
185/55R15	82	S	8.3	194	6J	585	475	1047	300 44	BSW
185/60R15	84	S	8.8	189	5 1/2J	603	500	1102	300 44	BSW
185/65R15	88	S	8.3	189	5 1/2J	621	560	1235	300 44	BSW
195/50R15	82	S	8.8	201	6J	577	475	1047	300 44	BSW
195/55R15	85	S	8.8	201	6J	595	515	1135	300 44	BSW
195/60R15	88	S	8.3	201	6J	615	560	1235	300 44	BSW
195/65R15	91	S	8.8	201	6J	635	615	1356	300 44	BSW
205/60R15	91	S	8.5	209	6J	627	615	1356	300 44	BSW
205/65R15	94	S	8.5	209	6J	647	670	1477	300 44	BSW
205/70R15	96	S	8.5	209	6J	669	710	1565	300 44	BSW
185/55R16	83	S	8.8	194	6J	610	487	1074	300 44	BSW
195/55R16	87	S	8.8	201	6J	620	545	1201	300 44	BSW
205/55R16	91	S	8.3	214	6 1/2J	632	615	1356	300 44	BSW
225/55R16	95	S	8.8	233	7J	654	690	1521	300 44	BSW
195/60R16	89	S	8.8	201	6J	640	580	1279	300 44	BSW
205/60R16	92	S	9.1	209	6J	652	630	1389	300 44	BSW
215/55R16	93	S	8.8	226	7J	642	650	1433	300 44	BSW
215/60R16	95	S	9.1	221	6 1/2J	664	690	1521	300 44	BSW
215/65R16	98	S	8.5	221	6 1/2J	686	750	1653	300 44	BSW
215/70R16	100	S	8.5	221	6 1/2J	708	800	1764	300 44	BSW
225/70R16 XL	107	S	8.5	228	6 1/2J	722	975	2149	340 50	BSW
235/70R16	106	S	8.5	240	7J	736	950	2094	300 44	BSW
215/45R17	91	S	8.8	213	7J	626	545	1201	300 44	BSW
215/50R17	95	S	8.8	226	7J	648	615	1356	300 44	BSW
215/60R17	96	S	8.5	221	6 1/2J	690	710	1565	300 44	BSW
225/45R17	94	S	8.8	225	7 1/2J	634	615	1356	300 44	BSW
225/50R17	94	S	8.8	233	7J	658	670	1477	300 44	BSW
215/55R17	98	S	8.8	226	7J	668	670	1477	300 44	BSW
225/55R17	97	S	8.8	233	7J	680	730	1609	300 44	BSW
235/55R17	99	S	8.8	245	7 1/2J	690	775	1709	300 44	BSW
225/60R17	99	S	8.5	228	6 1/2J	702	775	1709	300 44	BSW
225/65R17	102	S	8.5	228	6 1/2J	724	850	1874	300 44	BSW
235/65R17 XL	108	S	8.5	240	7J	738	900	1984	340 50	BSW
245/45R17	95	S	8.8	243	8J	652	690	1521	300 44	BSW
265/65R17	112	S	9.5	272	8J	776	1120	2469	300 44	BSW
285/65R17	116	S	9.5	292	8 1/2J	802	1250	2756	300 44	BSW
185/75R16C	104/102	R	10	184	5J	684	1800	3968	475 70	BSW
195/75R16C	107/105	Q	10	196	5 1/2J	698	1950	4299	475 70	BSW